


RQDR-AP**Tubing clamp systems for light, medium and heavy duty applications**

Rotatable tubing holder with screw-on plate / maximum mobility with red MOVE insert, especially for cobots and small industrial robots at slow and medium speeds in the field of robotics.



Temperature: -40°C ... +120°C

Material: PA plastics (PA6)

CHARACTERISTICS:

- Properties: rational tubing assembly for corrugated tubings with coarse and fine profile
- free of silicone, cadmium and halogen
- self-extinguishing
- fit for high mechanical stress
- impact-resistant
- REACH and RoHS compliant

**APPLICATIONS:**

- Robotics
- especially for Cobots and small industrial robots at slow and medium speeds.

FLEXA No.	Colour	OD [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	Ø G [mm]	Weight [kg/100]	PU [pcs.]
15040042201	Black	42.5	77.0	74.0	30.0	45.0	60.0	6.5	4.50	1
15040142201	Black	with MOVE OD 34.5	77.0	74.0	30.0	45.0	60.0	6.5	5.60	1
15040242201	Black	with MOVE OD 28.5	77.0	74.0	30.0	45.0	60.0	6.5	5.84	1
15040342201	Black	with MOVE OD 21.2	77.0	74.0	30.0	45.0	60.0	6.5	6.20	1
15040442201	Black	with RQMR OD 34.5	77.0	74.0	30.0	45.0	60.0	6.5	5.60	1
15040542201	Black	with RQMR OD 28.5	77.0	74.0	30.0	45.0	60.0	6.5	6.20	1
15040642201	Black	with RQMR OD 21.2	77.0	74.0	30.0	45.0	60.0	6.5	6.30	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.