



MELLOW LIGHT evolution EA

- LED ceiling-recessed luminaire for general and task area lighting
- Crystal Optic for optimum glare control to 4800 lm
- Diffuse side sections for pleasant ambient lighting
- Colour temperature 4000 K (intermediate) and 3000 K (warm white) and tunableWhite from 3000–6000 K
- Colour rendering Ra > 80 for office applications
- Chromaticity tolerance between multiple luminaires of up to 3 MacAdam ellipses
- EN12464-1 compliant for office applications with UGR < 19
- LED service life: 50000 h before luminous flux is reduced to 90 % of the initial value
- Luminaire pre-wired using halogen-free leads
- Please order the fixing kit separately for concealed ceiling systems and sawn-out holes
- Bluetooth® version: wireless connection via app with Bluetooth® 4.x - basicDim Wireless
- DALI-controllable ECG with 1 Dali address (wing and central section can be controlled together)
- Luminaire available in Colour Rendering Ra > 90 and Emergency Version via myMELLOW LIGHT EVO/INF

An Environmental Product Declaration (EPD) is available for the following products.

| | |
|--|----------|
| MLevo EA LED4800-840 M600L12 LDO KA WH | 42184756 |
| MLevo EA LED4800-840 M600Q LDO KA WH | 42184757 |
| MLevo EA LED4800-830 M600Q LDO KA WH | 42184938 |
| MLevo EA LED3600-840 M600L12 LDO KA WH | 42185169 |



Designer: Designed in Collaboration with Gensler