



## MELLOW LIGHT infinity EL

- LED ceiling-recessed luminaire for general and task area lighting
- High quality lenticular structure for a more uniform appearance
- Diffuse side sections for pleasant ambient lighting
- Colour temperature 4000 K (intermediate) and 3000 K (warm white) and tunableWhite from 3000–6000 K
- Colour rendering Ra > 80 for office applications
- Chromaticity tolerance between multiple luminaires of up to 3 MacAdam ellipses
- EN12464-1 compliant for office applications with UGR < 19
- LED service life: 50000 h before luminous flux is reduced to 90 % of the initial value
- Luminaire pre-wired using halogen-free leads
- Please order the fixing kit separately for concealed ceiling systems and sawn-out holes
- Bluetooth® version: wireless connection via app with Bluetooth® 4.x - basicDim Wireless
- DALI-controllable ECG with 2 Dali addresses (wing and central section can be separately controlled)
- Luminaire available in Colour Rendering Ra > 90 and Emergency Version via myMELLOW LIGHT EVO/INF

**An Environmental Product Declaration (EPD) is available for the following products.**

MLinf EL LED3600-840 M600Q LDO KA WH	42184770
MLinf EL LED3600-840 M600L12 LDO KA WH	42184954
MLinf EL LED3600-830 M600L12 LDO KA WH	42185206



Designer: Designed in Collaboration with Gensler