



## VIVO II-R M Ra >80

- Multifunctional LED recessed spotlight with stabilised colour temperature (warm white / neutral white)
- Optimised for efficient and high-output accent lighting in retail and automotive applications as well as architectural lighting
- With converter for ceiling recessing
- Die-cast aluminium spotlight housing
- Colour: black or white microtextured paint, other colours such as matt silver, concrete grey, chrome-colour or cooper-colour are possible as variants
- Multi-functional light head rotating through 357° and swivelling in/out (-20°/+60°)
- Excellent glare control via front ring made of PC, black or white, other colours such as concrete grey, chrome-colour or copper-colour are possible as variants
- Front ring accommodates the accessories (optical, protective glass, honeycomb louvre)
- Specular reflector of aluminised PC, highly specular, iridescence-free
- Recessed ring made of polycarbonate
- 50000 h service life at 80 % luminous flux
- stableWhite colour temperature: 3000 K (LED830: warm white) or 4000 K (LED840: intermediate)
- Colour rendering index: Ra > 80
- Luminaire luminous flux: 2800 lm (28 W)
- Luminaire efficiency: 83–93 lm/W
- Control: switchable, dimmable Dali only as well as wireless connection via app with Bluetooth® 4.x - basicDim Wireless as variant
- Mains voltage: 220–240 V / 50/60 Hz
- 2-pole connection terminal, loop-in/loop-out can be ordered as variant
- Mounting: mounting ring with anti-slip catches for tool-free installation in ceilings with ceiling thicknesses 1–25 mm
- Specular reflector designed to be interchangeable

### Accessory

DVR DA175	60800315
V2 M BOPT	60700425
V2 M HONEYCOMB LOUVRE BK	60700426
V2 M OVAL OUTLINE LENS	60700427
V2 M PROTECTION GLASS	60700428
V2 M REFL FL	60700432
V2 M REFL MSP	60700431
V2 M REFL SP	60700430
V2 M REFL VFL	60700434
V2 M REFL WFL	60700433
V2 M SOFT OUTLINE LENS	60700429
V2 M VOPT	60700435



Designer: EOOS

