



VIVO II-SR L Ra > 80

- Multifunctional LED semi-recessed spotlight with stabilised colour temperature (warm white / neutral white)
- Optimised for efficient and high-output accent lighting in retail and automotive applications as well as architectural lighting
- With converter for ceiling recessing
- Die-cast aluminium spotlight housing
- Colour: black or white microtextured paint, other colours such as matt silver, concrete grey, chrome-colour or cooper-colour are possible as variants
- Multifunctional lamp unit rotates through 360° and tilts through 90°
- Excellent glare control via front ring made of PC, black or white, other colours such as concrete grey, chrome-colour or copper-colour are possible as variants
- Front ring accommodates the accessories (optical, protective glass, honeycomb louvre)
- Specular reflector of aluminised PC, highly specular, iridescence-free
- 50000 h service life at 80 % luminous flux
- stableWhite colour temperature: 3000 K (LED830: warm white) or 4000 K (LED840: intermediate)
- Colour rendering index: Ra > 80
- Luminaire luminous flux: 4100-4900 lm
- Luminaire efficiency: 83-93 lm/W
- Control: switchable, dimmable Dali only as well as wireless connection via app with Bluetooth® 4.x - basicDim Wireless as variant
- Mains voltage: 220-240 V / 50/60 Hz
- Specular reflector designed to be interchangeable
- Mounting: mounting ring, ceiling thickness 1-40mm



Designer: EOOS

