



## ONDARIA II LED Opal



- Decorative round luminaire with uniform backlighting of opal cover
- Aluminium housing in white painted finish
- Opal plastic cover of PMMA
- Available in four sizes: small (Ø 400 mm), medium (Ø 590 mm), large (Ø 870 mm), X-large (Ø 1150 mm)
- Low indirect component for ceiling/wall illumination
- Colour temperature 4000 K (intermediate) and 3000 K (warm white)
- LED service life: 50000 h before luminous flux is reduced to 90 % of the initial value
- Chromaticity tolerance between multiple luminaires of up to 3 MacAdam ellipses
- Bluetooth® version: wireless connection via app with Bluetooth® 4.x - basicDim Wireless
- Luminaire pre-wired using halogen-free leads
- Can be fitted as recessed or pendant luminaire using special accessory (please order separately)

### **An Environmental Product Declaration (EPD) is available for the following products.**

ONDA2 A D590 LED3600-830 LDE WH	42184835
ONDA2 A D870 LED8000-830 LDE WH	42184836
ONDA2 A D1150 LED14000-830 LDE WH	42184837
ONDA2 A D590 LED5800-840 LDE WH	42184838
ONDA2 D400 LED1600-830 LDE WH	42186624
ONDA2 P D870 LED8000-840 LDE WH	42184845
ONDA2 P D1150 LED14000-840 LDE WH	42184846
ONDA2 P D590 LED3600-830 LDE WH	42184847
ONDA2 P D590 LED5800-840 LDE WH	42184850
ONDA2 E D870 LED12000-830 LDE WH	42184866



Designer: Studio Ambrozus

