



LANOS S OPAL

- Decorative circular luminaire with uniform back light of the opal (or alternatively microprismatic) light emission surface
- Gentle indirect component for atmospheric ceiling illumination (also available without backlight effect)
- Unique HALO effect makes the luminaire extremely versatile due to separate control of the outer rim LEDs and the central LEDs of the direct light. Outer rim can be used as a Nightlight.
- Colour temperature 3000 K (warm white), 4000 K (cool white) and tunableWhite from 2700 K to 6500 K
- Tunable White option (2700-6500K) enables colour adjustments to create atmosphere and ambience
- Colour Rendering Ra >90 (also available as Ra >80 on request)
- Luminaires in Small (Ø320mm), for customized lighting concepts
- Premium luminaire housing made of polycarbonate (PC) available in five decorative bezel colours (Black, White, Silver, Bronze and Anthracite)
- Surface-mounted wall and ceiling luminaire can be suspended via tube suspension with separately orderable pendant sets
- Simple mounting due to removable, first-to-mount gear tray and easy-fit luminaire body
- Elegant design paired with a robust exterior: protection rating IP54 / impact resistance IK08.
- Luminaire also available with Zumtobel Spectrum technology

An Environmental Product Declaration (EPD) is available for the following products.

LANOS S 1400-940 OP DI LDE WH	42188118
LANOS S 1900-940 OP DI LDE WH	42188119
LANOS S 1400-927-65 OP DI LDE WH	42188221