

Nella

Simple and elegant post-top luminaire solution, ideal for refurbishment projects

- A contemporary design created with Dark Sky principles in mind, offering <1% ULOR
- A robust and reliable lantern with an integrated surge protection device
- Simplified control via onboard switch to adjust the lumen output intensity to suit the application
- Supplied pre-wired and with tool-free access to the luminaire for ease of installation and ongoing maintenance



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.

Material/Finish

Canopy and brackets: die cast aluminium

Finish: powder coated anthracite Enclosure: tempered glass

Standard corrosion class C3 according to ISO 9223: 2012.

Installation/Mounting

Luminaire: Supplied complete and ready to install, in a single box. Mounting on a standard 60mm column at 3 to 4,5 meters height. Pre-wired with 4 meter cable for ease of installation. Tool-free opening at the top.

Specification

To specify state:

A performance lantern with <1% upward lighting emission available in 3000K. Ideal for building surrounds, residential and urban areas, parks and plazas.

As Thorn Nella

Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
Nella				
NELLA 3000-730 R-S CL2 T60 ANT	LED		10	96636345
NELLA 3000-730 STR-A CL2 T60 ANT	LED		10	96636346